§ 172.542

(b) In addition to complying with §172.519, the background on the POISON GAS placard and the symbol must be white. The background of the upper diamond must be black and the lower point of the upper diamond must be 65 mm (25% inches) above the horizontal center line. The text, class number, and inner border must be black.

[62 FR 39408, July 22, 1997]

§172.542 FLAMMABLE placard.

(a) Except for size and color, the FLAMMABLE placard must be as follows:



- (b) In addition to complying with §172.519, the background color on the FLAMMABLE placard must be red. The symbol, text, class number and inner border must be white.
- (c) The word "GASOLINE" may be used in place of the word "FLAM-MABLE" on a placard that is displayed on a cargo tank or a portable tank being used to transport gasoline by highway. The word "GASOLINE" must be shown in white.

[Amdt. 172-123, 56 FR 66262, Dec. 20, 1991]

§172.544 COMBUSTIBLE placard.

(a) Except for size and color, the COMBUSTIBLE placard must be as follows:



- (b) In addition to complying with §172.519, the background color on the COMBUSTIBLE placard must be red. The symbol, text, class number and inner border must be white. On a COMBUSTIBLE placard with a white bottom as prescribed by §172.332(c)(4), the class number must be red or black.
- (c) The words "FUEL OIL" may be used in place of the word "COMBUS-TIBLE" on a placard that is displayed on a cargo tank or portable tank being used to transport by highway fuel oil that is not classed as a flammable liquid. The words "FUEL OIL" must be white.

[Amdt. 172–123, 56 FR 66262, Dec. 20, 1991]

§172.555 POISON INHALATION HAZ-ARD placard.

(a) Except for size and color, the POI-SON INHALATION HAZARD placard must be as follows: